

DATA SHEET REV 3 OF 2016 UOD/S03

1 PRODUCT IDENTIFICATION AND COMPANY NAME

Product Name : Universal Paints Urethane Floor Coating

Product Identification: Air drying high gloss finish

Supplier/Manufacturer: Universal Coatings (Pty) Ltd **Contact**: R. Diab,

G. Murchie

Kya Sands Randburg South Africa

2 COMPOSITION/INFORMATION ON INGREDIENTS

Resin Base : Alkyd resin

Hazardous Components : Hydrocarbon solvent blend containing

Mineral Turpentine <10% CAS No 64742-88-7 EC No 649-405-00-X

R Phrases R10, 20/21/65 **S Phrases** S2. 13, 43, 62

3 HAZARDS IDENTIFICATION

SAPMA Health Rating Physical/Chemical Hazards Human Health Hazards 3 Slight-Irritation or minor reversible injury possible

This paint is FLAMMABLE

: Respiration : May cause irritation, dizziness, nausea and

loss of consciousness.

Eyes: May cause moderate irritation.

: Ingestion : May cause gastro-intestinal irritation, dizziness,

nausea and loss of consciousness.

: Skin : May cause sensitization. May also be a skin

irritant and repeated contact may increase this

effect.

Environmental Hazards : Toxic to aquatic organisms. May cause short-term adverse effects

in the aquatic environment.

No carcinogenic, mutagenic or genetic effects established.



4 FIRST AID MEASURES

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never

give anything by mouth to an unconscious person.

Inhalation: Move to a safe area with fresh air. Keep person warm and at rest. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

respiration or oxygen by a trained person. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.

Eye Contact

Rinse thoroughly with potable water for at least 10 minutes.

Ingestion

Do not induce vomiting. Keep person warm and at rest. Seek medical advice

immediately and show this Safety Data Sheet to the medical officer.

Skin Contact

Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use a recognized skin cleanser. Do not use solvents or thinners.

FLOOR COAT Page 1 of 4



DATA SHEET REV 3 OF 2016 UOD/S03

5 FIRE-FIGHTING MEASURES

Extinguishing Media : Use foam, CO2, dry powders and water mist. Do NOT use a high

pressure water jet.

Recommendations: Decomposed products are a health hazard. Use appropriate breathing

apparatus. Cool closed containers exposed to fire with Foam not water

Jets to prevent ignition.

6 ACCIDENTAL RELEASE MEASURES

Personal Precautions : Ventilate the area. Avoid breathing in vapours. Remove all sources of

ignition e.g. flames, sparks, static electricity and heat.

Spill : Contain and collect spillage with absorbent material. Dispose of

according to local regulations. Do not allow spillage to enter sewerage

drains or watercourses.

7 HANDLING AND STORAGE

Handling: Keep container tightly closed. Keep away from heat, sparks and flame.

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. After handling the material, workers should

wash hands and face before eating, drinking and smoking.

Always comply with health and safety regulations.

Storage : Store in original container. Observe label precautions. Store in a cool, well-

ventilated area away from incompatible materials and ignition sources.

Keep away from oxidizing agents, strong alkaline and acids.

No smoking. Containers which have been opened must be carefully resealed

and kept upright to prevent leakage.

8 EXPOSURE CONTROL/PERSONAL PROTECTION

Engineering Measures: Provide adequate ventilation. Where reasonably practicable

this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapour below the OEL, suitable respiratory

protection must be worn.

Personal Protective Equipment

Respiration

Eyes

Ingestion

Should ventilation be inadequate or if workers are exposed

to concentrations above the exposure limit, appropriate

certified respirators must be used.

: Use safety eyewear designed to protect against splash of

liquids. Never touch eyes with dirty hands or gloves.

: Observe the rules of hygiene. Wash hands and face before

eating, drinking or smoking.

Skin : Use protective gloves. Wash immediately in case of

contact.

Environmental Exposure Control: Do not allow product to enter sewerage drains or

watercourses.







FLOOR COAT Page 2 of 4



DATA SHEET REV 3 OF 2016 UQD/S03

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Opaque Liquid Flash Point (° Celsius) : 37 ° Celsius

Solubility: Hydrocarbon solvents, Insoluble In Water

Viscosity : 67 - 72 KU

10 STABLILTY AND REACTIVITY

Stability : Stable under recommended storage and handling conditions.Conditions to Avoid : Ignition sources, flames, sparks, static and heat (use Earthing).

Materials to Avoid : Oxidizing agents, strong alkaline or acidic materials.

Inert no reaction with firefighting water.

11 TOXICOLOGICAL INFORMATION

Frequent and prolonged skin contact may cause irritation and skin inflammation.

- Prolonged inhalation of vapours in high concentrations may lead to headache, giddiness and nausea.
- In case of contact with the product, danger of absorption through the skin, irritation of the skin/mucous membranes.
- No carcinogenic, mutagenic or genetic effects established.

12 ECOLOGICAL INFORMATION

- There is no data available on the preparation itself. But it may have short term environmental effect; contain, monitor and remove.
- Product is considered a water pollutant. Do not allow to enter drains or watercourses.

13 DISPOSAL CONSIDERATIONS

- Do not allow to enter drains or watercourses.
- Dispose of according to state and local applicable regulations.
- Exercise Caution in the disposal of used containers.

14 TRANSPORT INFORMATION

SIN/UN Number : 1263 Shipping Name : Paint Packaging Group : III Class : 3



FLOOR COAT Page 3 of 4



DATA SHEET REV 3 OF 2016 UOD/S03

15 REGULATORY INFORMATION

R10 : Flammable

R20/21 : Harmful by inhalation and contact with the skin

R65 : May be harmful if swallowed S2 : Keep out of reach of children

\$13 : Keep away from food, drink and animal feed stuffs

\$43 : In case of fire, use fog, foam or powder - Do Not use water jets

S62 : If swallowed, do not induce vomiting but seek medical advice immediately.

16 OTHER INFORMATION

Date of Printing : November 2016 **Date if Issue** : November 2016

Revision : 3

Notice : Take precautionary measures against static discharges.

In case of any discomfort always seek medical advice.

The information in this SDS is based on the present state of our knowledge and on current national laws. The product is not to be used for purposes other than those specified under Section 1. without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product — it is not to be considered as a guarantee of the product's properties. No responsibility is accepted for errors or omissions or the consequences

thereof.

FLOOR COAT Page 4 of 4