

# SAFETY DATA SHEET

DATA SHEET REV 3 OF 2016 UOD/W11

# 1 PRODUCT IDENTIFICATION AND COMPANY NAME

Product Name : Universal Paints Galvanised Primer (Grey & Red)

**Product Identification**: Air drying emulsion paint

Supplier/Manufacturer : Universal Coatings (Pty) Ltd Contact : R. Diab,

G. Murchie

(+27) 11 - 462 4293

**Address** : 19 Staal Street **Tel** : (+27) 11 – 462 4284

Kya Sands Randburg South Africa

COMPOSITION/INFORMATION ON INGREDIENTS

Chemical ClassEmulsion Based PaintClassificationNot classed as hazardous

R Phrases None S Phrases S2, 24/25

Hazardous Components No significant quantity of any classified hazardous substance

present.

# 3 HAZARDS IDENTIFICATION

SAPMA Health Rating : 4-Minimal –No great risk to health.

Human Health Hazards : Inhalation : Avoid exposure to vapours, fumes and mists.

Eyes : May cause slight irritation, any possible contact

to be avoided.

Ingestion : May cause irritation and nausea.

Skin : No hazard expected if used in moderation,

Fax

direct contact to be avoided.

**Environmental Hazards**: No records of chronic effects found, so considered low hazard.

Non-toxic but can have undesirable environmental side effects so

a lot of care must be taken with disposal.



# 4 FIRST AID MEASURES but

General: In all cases of doubt, or when symptoms persist, seek medical attention. Never

give anything by mouth to an unconscious person.

**Inhalation**: Move to a safe area with fresh air. Keep person warm and at rest. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

respiration or oxygen by trained personnel. Give nothing by mouth. If

unconscious, place in recovery position and seek medical advice.

Eye Contact
 Ingestion
 Rinse thoroughly with water for at least 10 minutes. Seek medical attention.
 Do not induce vomiting. Keep person warm and at rest. Seek medical advice

immediately and show the container or label.

**Skin Contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use a recognized skin cleanser. Do not use solvents or thinners.

GALVANISED PRIMER Page 1 of 3



# SAFETY DATA SHEET

DATA SHEET REV 3 OF 2016 UOD/W11

# 5 FIRE-FIGHTING MEASURES

- This paint is NOT flammable but the dry residue is combustible.
- Expect no direct explosion hazard. Use CO2, dry powder or foam.

# 6 ACCIDENTAL RELEASE MEASURES-also see sections 5.8 and 13

**Personal Precautions** 

: Ventilate the area. Avoid breathing in vapors.

Spill

Storage

: Contain and collect spillage with absorbent material. Dispose of

according to local regulations. Do not allow spillage to enter sewerage

drains or watercourses.

# 7 HANDLING AND STORAGE- General This is an Inert with no special requirements for hazard Containment

**Handling**: Keep container tightly closed. Eating, drinking and smoking should be

prohibited in area where this material is handled, stored and processed. After handling the material, workers should wash hands and face before eating, drinking and smoking. Always comply with health and safety regulations.

: Store in original container. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources.

Keep away from oxidizing agents, strong alkaline and acids.

No smoking. Containers which have been opened must be carefully resealed

and kept upright to prevent leakage.

# 8 EXPOSURE CONTROL/PERSONAL PROTECTION

SAPMA Rating

Personal Protective Equipment

Respiration

4-H-C

Should ventilation be inadequate or if workers are exposed to concentrations above the exposure limit, appropriate

certified respirators must be used.

Eyes : Use safety eyewear designed to protect against splash of

liquids. Never touch eyes with dirty hands or gloves.

Ingestion : Observe the rules of hygiene. Wash hands and face before

eating, drinking or smoking.

**Skin** : Use protective gloves. Wash in case of contact.







# 9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Viscous Opaque Liquid : Not flammable-N/A

Density : Water

Density : 1.15-1.35

pH : 8.5-9.5

# 10 STABLILTY AND REACTIVITY

Stability : Stable under recommended storage and handling conditions.

**Conditions to Avoid** : Excessive heat – store below 30° Celsius.

Materials to Avoid : Oxidizing agents, strong alkaline or acidic materials.

GALVANISED PRIMER Page 2 of 3



# SAFETY DATA SHEET

DATA SHEET REV 3 OF 2016 UOD/W11

# 11 TOXICOLOGICAL INFORMATION

No records of chronic effects found. .

# 12 ECOLOGICAL INFORMATION

Product is considered a water pollutant. Do not allow to enter drains or watercourses.

# 13 DISPOSAL CONSIDERATIONS

- Do not allow to enter drains or watercourses.
- Dispose according to national and local applicable regulations.
- Empty containers are suitable for recycling, but caution must be exercised in the disposal of used containers.

# 14 TRANSPORT INFORMATION

**SIN/UN Number**: Not classified as dangerous for transport.

Shipping Name : Not classified.
Packaging Group : Not classified.

Class : Not classified as hazardous.

# 15 REGULATORY INFORMATION

Classification : Not classified as hazardous.

S2 : Keep out of reach of children.

S24/25 : Avoid contact with eyes and skin.

# 16 OTHER INFORMATION

**Date of Printing** : November 2016 **Date if Issue** : November 2016

Revision : 3

Notice : Take precautionary measures against static discharges.
In case of any discomfort always seek medical advice.

The information in this SDS is based on the present state of our knowledge and on current national laws. The product is not to be used for purposes other than those specified under Section 1. without first obtaining written handling instructions. It is always the responsibility of the user to take all necessary steps in order to fulfill the demand laid down in the local rules and legislation. The information in this SDS is meant as a description of the safety requirements of our product – it is not to be considered as a guarantee of the product's properties. No responsibility is accepted for errors or omissions or the consequences

thereof.

GALVANISED PRIMER Page 3 of 3