



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

# ACRYLIC CRACK FILLER

PRODUCT CODE: ACR00

TECHNICAL DATA SHEET

November 2016.R3

<ul style="list-style-type: none"> <li>• <b>Product Description</b></li> </ul>	<ul style="list-style-type: none"> <li>• A versatile water based crack-patching compound for filling cracks and holes in exterior and interior walls.</li> </ul>						
<ul style="list-style-type: none"> <li>• <b>Application Areas</b></li> </ul>	<ul style="list-style-type: none"> <li>• To help seal vertical and horizontal cracks in walls (up to a maximum of 3mm), which even after filling may have a tendency to re-open with time.</li> <li>• Interior and exterior use.</li> </ul>						
<ul style="list-style-type: none"> <li>• <b>Product Features</b></li> </ul>	<ul style="list-style-type: none"> <li>• Provides excellent flexibility and durability.</li> <li>• Highly water resistant-with a low water up take.</li> <li>• Low odour.</li> </ul>						
<ul style="list-style-type: none"> <li>• <b>Product Data</b></li> </ul>	<table border="1"> <tr> <td>Resin Base</td> <td>Acrylic resin emulsion</td> </tr> <tr> <td>Drying Time</td> <td>Touch dry: ± 30 minutes</td> </tr> <tr> <td>Film Thickness</td> <td>Fills cracks up to 3mm.</td> </tr> </table>	Resin Base	Acrylic resin emulsion	Drying Time	Touch dry: ± 30 minutes	Film Thickness	Fills cracks up to 3mm.
Resin Base	Acrylic resin emulsion						
Drying Time	Touch dry: ± 30 minutes						
Film Thickness	Fills cracks up to 3mm.						
<ul style="list-style-type: none"> <li>• <b>Application Details</b></li> </ul>							
<ul style="list-style-type: none"> <li>• <b>Application Method</b></li> </ul>	<ul style="list-style-type: none"> <li>• Utilise a spatula, scraper or trowel.</li> </ul>						
<ul style="list-style-type: none"> <li>• <b>Thinning</b></li> </ul>	<ul style="list-style-type: none"> <li>• Not to be thinned.</li> </ul>						
<ul style="list-style-type: none"> <li>• <b>Cleaning</b></li> </ul>	<ul style="list-style-type: none"> <li>• Clean up with water immediately after use.</li> </ul>						
<ul style="list-style-type: none"> <li>• <b>General Application</b></li> </ul>	<ul style="list-style-type: none"> <li>• Smooth product within 30 minutes of application.</li> <li>• The patched areas may be over-coated using any Universal water-based finish, <b>Universal Bonding Liquid</b> or <b>Universal Pigmented Plaster Primer</b> (after curing 24 hours).</li> <li>• Make sure surface is dry and firm.</li> <li>• Ensure that all cracks are “V” out.</li> </ul>						
<ul style="list-style-type: none"> <li>• <b>Colour Range and Quantities</b></li> </ul>	<p><b>Universal Acrylic Crack Filler</b> is off-white in colour. Available in 1ℓ, 5ℓ &amp; 20ℓ.</p>						
<ul style="list-style-type: none"> <li>• <b>Precautions</b></li> </ul>	<p><b>Universal Acrylic Crack Filler</b> is non-flammable. It contains no toxic substances and very low levels of VOC.</p>						
<ul style="list-style-type: none"> <li>• <b>Disclaimer</b></li> </ul>	<p>Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.</p>						

**Universal Coatings (PTY) LTD**  
Reg No. 1982/10922/07

**19 Staal Street  
Kya Sands, Randburg  
South Africa**

**Tel. +(27) 11- 462 4284  
www.universalphaints.co.za**