



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

ACRYLIC SEALER

PRODUCT CODE: ACR00

TECHNICAL DATA SHEET

November 2016.R3

Product Description	<ul style="list-style-type: none"> • Universal Acrylic Sealer is a water based binder used as a base coat on various substrates before the application of acrylic top coats. • As a base coat on roof tiles, to close pores, before applying 2 coats of Universal Roof Acrylic. • As a base coat on weathered previously painted PVA on plastered walls. Also used on dried plaster before application of two top coats of Universal Acrylic Paint of your choice.. 						
Application Areas	<ul style="list-style-type: none"> • Roof Tiles. • Raw Plaster. • Weathered previously painted plaster. 						
Product Features	<ul style="list-style-type: none"> • Good bonding properties. • Excellent adhesion. • Low odour. 						
Product Data	<table border="1"> <tr> <td>Resin Base</td> <td>Acrylic resin emulsion</td> </tr> <tr> <td>Drying Time</td> <td>Touch dry +- 30 minutes Hard dry 3-4 hours</td> </tr> <tr> <td>Film Thickness</td> <td>35–50° microns</td> </tr> </table>	Resin Base	Acrylic resin emulsion	Drying Time	Touch dry +- 30 minutes Hard dry 3-4 hours	Film Thickness	35–50° microns
Resin Base	Acrylic resin emulsion						
Drying Time	Touch dry +- 30 minutes Hard dry 3-4 hours						
Film Thickness	35–50° microns						
Application Details	<ul style="list-style-type: none"> • Apply by roller or brush - one coat only. • Allow to dry for a minimum of 3 hours before application of top coats, if air temperature drops below 10° Celsius during winter. • Allow 24 hours to dry before applying top coats. 						
Mixing	<ul style="list-style-type: none"> • Always stir well before use with a flat paddle. 						
Application Method	<ul style="list-style-type: none"> • Brush or Roller. 						
Thinning	<ul style="list-style-type: none"> • Universal Acrylic Sealer is ready for use. 						
Cleaning	<ul style="list-style-type: none"> • Rinse thoroughly with warm water. 						
Uncoated Concrete Surfaces	<ul style="list-style-type: none"> • Apply one coat of Universal Acrylic Sealer for best results. 						
Previously Painted Surfaces	<ul style="list-style-type: none"> • Surface to be coated must be dry and firm, free of loose particles, dust, algae and fungal growth. 						
Colour Range and Quantities	<ul style="list-style-type: none"> • Universal Acrylic Sealer is a clear liquid. • Universal Acrylic Sealer is available in 1ℓ, 5ℓ and 20ℓ. 						
Precautions	<ul style="list-style-type: none"> • Universal Acrylic Sealer should not be used on lime containing surfaces or on Gypsum Plaster. • Best application for the above is Universal Pigmented Plaster Primer. 						
Disclaimer	Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.						
<p>Universal Coatings (PTY) LTD Reg No. 1982/10922/07</p>							
<p>19 Staal Street Kya Sands, Randburg South Africa</p>	<p>Tel. +(27) 11- 462 4284 www.universalphaints.co.za</p>						