



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

DAMP SEALER
PRODUCT CODE: DMP00
TECHNICAL DATA SHEET
November 2016.R3

<ul style="list-style-type: none"> • Product Description 	<ul style="list-style-type: none"> • A new generation solvent based solution acrylic waterproofing compound, in which white cement is incorporated into the ready to use liquid coating to provide a long lasting, seamless and flexible waterproof coating for parapet walls and other areas as required.
<ul style="list-style-type: none"> • Application Areas 	<ul style="list-style-type: none"> • Any area with a history of rising damp. • Parapet walls.
<ul style="list-style-type: none"> • Product Features 	<ul style="list-style-type: none"> • Highly water resistant – with a good water barrier – this coating will not let the water push the subsequent coatings off the wall due to rising damp. • Excellent adhesion and over coat ability. • Resists algae and fungal growth.
<ul style="list-style-type: none"> • Application Details 	<ul style="list-style-type: none"> • Any area with a history of rising damp. • Parapet walls.
<ul style="list-style-type: none"> • Application Method 	<ul style="list-style-type: none"> • With a brush apply a generous coat of Universal Damp Sealer to the area, which needs protecting. • Allow to dry 18 – 24 hours. • If required brush apply a second generous coat. • Allow the system to dry for at least 24 hours preferably longer in cold or very humid weather. • Overcoat the entire area using any Universal water based finish, Universal Bonding Liquid or Universal Pigmented Plaster Primer (after curing 24 hours). • Check that all joints and cracks are well sealed.
<ul style="list-style-type: none"> • Surface Preparation 	<ul style="list-style-type: none"> • Cement plaster fill and seal all visible cracks. • Allow to dry.
<ul style="list-style-type: none"> • Previously Painted Surfaces • Concrete • Precast • Plaster 	<ul style="list-style-type: none"> • Remove all loose, flaking and bubbling paint. • Remove all dust, foreign material, and fungal and algae growth. • Allow to dry.
<ul style="list-style-type: none"> • General 	<ul style="list-style-type: none"> • Do not apply before 9:00Hr and after 16:00Hr in winter. • Do not apply if it looks like rain will occur within 4 – 6 hours of application. • Universal Damp Sealer is normally applied by brush. • One, preferably two coats of Universal Damp Sealer are used. • Application equipment to be cleaned with Universal Mineral Turpentine.
<ul style="list-style-type: none"> • Precautions 	<ul style="list-style-type: none"> • This product is flammable and has a flash point of 37° Celsius.
<ul style="list-style-type: none"> • Disclaimer 	<p>Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.</p>

Universal Coatings (PTY) LTD
Reg No. 1982/10922/07

19 Staal Street
Kya Sands, Randburg
South Africa

Tel. +(27) 11- 462 4284
www.universalpaints.co.za

