



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

UNIVERSAL PIGMENTED PLASTER PRIMER

PRODUCT CODE: PRI00

TECHNICAL DATA SHEET

October 2018.R3

<ul style="list-style-type: none"> • Product Description 	<ul style="list-style-type: none"> • A classical solvent based interior, exterior plaster primer for masonry, cement, and plaster substrates and Rhinolite or gypsum Plaster. • For use under a range of Universal Paints topcoats. 				
<ul style="list-style-type: none"> • Application Areas 	<ul style="list-style-type: none"> • New and weather plaster, hardboard and fibre cement walls. 				
<ul style="list-style-type: none"> • Product Features 	<ul style="list-style-type: none"> • Serves as both a sealer and a primer. • Excellent adhesion to a range of substrates. • Excellent, no mess application properties. • High hiding power and film build. • High Alkali Barrier • Not suitable for: <ul style="list-style-type: none"> ○ Rhinoboard or paper covered ceiling / dry wall board ○ Metallic substrates (including Bishop or H-strips, nails & screws) 				
<ul style="list-style-type: none"> • Product Data 	<table border="1"> <tr> <td>Resin Base</td> <td>Thermoplastic Resin</td> </tr> <tr> <td>Drying Time</td> <td>4 – 6 hours</td> </tr> </table>	Resin Base	Thermoplastic Resin	Drying Time	4 – 6 hours
Resin Base	Thermoplastic Resin				
Drying Time	4 – 6 hours				
<ul style="list-style-type: none"> • Application Details 	<ul style="list-style-type: none"> • With a brush, mohair roller or airless spray. • Apply a generous coat of Universal Pigmented Plaster Primer to the area which needs protecting. • Allow to dry 18 -24 hours before recoating. • Clean up application equipment with Universal Mineral Turpentine or brush cleaner. • Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. • Do not eat, drink or smoke while applying. 				
<ul style="list-style-type: none"> • Mixing 	<ul style="list-style-type: none"> • Always stir well using a flat paddle. 				
<ul style="list-style-type: none"> • Application Method 	<ul style="list-style-type: none"> • Brush or roller. 				
<ul style="list-style-type: none"> • Thinning 	<ul style="list-style-type: none"> • Thinning is not recommended. 				
<ul style="list-style-type: none"> • Cleaning 	<ul style="list-style-type: none"> • Use Universal Mineral Turpentine. 				
<ul style="list-style-type: none"> • General Application 	<ul style="list-style-type: none"> • Do not apply before 9:00Hr and after 16:00Hr in winter. • Do not apply to exterior if it looks like rain will occur with 4 – 6 hours of application. • Universal Pigmented Plaster Primer Is ready for use un-thinned; thinning will reduce its hiding power. • Although the spreading rate will vary with porosity and type of substrate. For uncoated new work the spread rate for Universal Pigmented Plaster Primer is 4 – 6m² /litre. • Clean up application equipment with Universal Mineral Turpentine. 				
<ul style="list-style-type: none"> • Uncoated Concrete Surfaces • Raw / New Plaster • Precast 	<ul style="list-style-type: none"> • Remove all dust, foreign material, fungal, algae growth. • Fill and seal all visible cracks and coat with Universal Pigmented Plaster Primer. • Remove all dust, foreign material, fungal and algae growth. • Fill and seal all visible cracks and coat with Universal Pigmented Plaster Primer. 				
<ul style="list-style-type: none"> • Previously Painted Surfaces 	<ul style="list-style-type: none"> • Remove all loose, flaking and bubbling paint. • Remove all dust, grease, foreign material, fungal and algae growth. 				

Pigmented Plaster Primer

Page 1 of 2

The **COLOUR** *of Quality.*

<ul style="list-style-type: none"> • Concrete • Precast • Plaster 	<ul style="list-style-type: none"> • Allow to dry. If then powdery or friable, seal with Universal Pigmented Plaster Primer.
<ul style="list-style-type: none"> • Colour Range and Quantities 	<ul style="list-style-type: none"> • Opaque Liquid • Available in 1l, 5l and 20l.
<ul style="list-style-type: none"> • Precautions 	<ul style="list-style-type: none"> • This product is highly flammable and has a flashpoint of 37° Celsius.
<ul style="list-style-type: none"> • Disclaimer 	<p>Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.</p>
<p>Universal Coatings (PTY) LTD Reg No. 1982/10922/07</p>	
<p>19 Staal Street Kya Sands, Randburg South Africa</p>	<p>Tel. +(27) 11- 462 4284 www.universalphaints.co.za</p>