



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

# UNIVERSAL PIGMENTED PLASTER PRIMER

PRODUCT CODE: PRI00

TECHNICAL DATA SHEET

November 2016.R3

<ul style="list-style-type: none"> <li>• <b>Product Description</b></li> </ul>	<ul style="list-style-type: none"> <li>• A classical solvent based interior, exterior plaster primer for masonry, cement, and plaster substrates.</li> <li>• For use under a range of Universal Paints topcoats.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Application Areas</b></li> </ul>	<ul style="list-style-type: none"> <li>• New and weather plaster, hardboard and fibre cement walls.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Product Features</b></li> </ul>	<ul style="list-style-type: none"> <li>• Serves as both a sealer and a primer.</li> <li>• Excellent adhesion to a range of substrates.</li> <li>• Excellent, no mess application properties.</li> <li>• High hiding power and film build.</li> <li>• Alkali resistant.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Product Data</b></li> </ul>	<table border="1"> <tr> <td><b>Resin Base</b></td> <td>Thermoplastic Resin</td> </tr> <tr> <td><b>Drying Time</b></td> <td>4 – 6 hours</td> </tr> </table>	<b>Resin Base</b>	Thermoplastic Resin	<b>Drying Time</b>	4 – 6 hours
<b>Resin Base</b>	Thermoplastic Resin				
<b>Drying Time</b>	4 – 6 hours				
<ul style="list-style-type: none"> <li>• <b>Application Details</b></li> </ul>	<ul style="list-style-type: none"> <li>• With a brush, mohair roller or airless spray (thin 20% with <b>Universal Mineral Turpentine</b>).</li> <li>• Apply a generous coat of <b>Universal Pigmented Plaster Primer</b> to the area which needs protecting.</li> <li>• Allow to dry 18 -24 hours before recoating.</li> <li>• Clean up application equipment with <b>Universal Mineral Turpentine</b> or brush cleaner.</li> <li>• Only apply in ventilated areas, keep away from all ignition sources, flames and sparks.</li> <li>• Do not eat, drink or smoke while applying.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Mixing</b></li> </ul>	<ul style="list-style-type: none"> <li>• Always stir well using a flat paddle.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Application Method</b></li> </ul>	<ul style="list-style-type: none"> <li>• Brush or roller.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Thinning</b></li> </ul>	<ul style="list-style-type: none"> <li>• Thinning is not recommended.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Cleaning</b></li> </ul>	<ul style="list-style-type: none"> <li>• Use <b>Universal Mineral Turpentine</b>.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>General Application</b></li> </ul>	<ul style="list-style-type: none"> <li>• Do not apply before 9:00Hr and after 16:00Hr in winter.</li> <li>• Do not apply to exterior if it looks like rain will occur with 4 – 6 hours of application.</li> <li>• <b>Universal Pigmented Plaster Primer</b> Is ready for use un-thinned; thinning will reduce its hiding power.</li> <li>• Although the spreading rate will vary with porosity and type of substrate. For uncoated new work the spread rate for <b>Universal Pigmented Plaster Primer</b> is 4 – 6m<sup>2</sup> /litre.</li> <li>• Clean up application equipment with <b>Universal Mineral Turpentine</b>.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Uncoated Concrete Surfaces</b></li> <li>• <b>Raw / New Plaster</b></li> <li>• <b>Precast</b></li> </ul>	<ul style="list-style-type: none"> <li>• Remove all dust, foreign material, fungal, algae growth.</li> <li>• Fill and seal all visible cracks and coat with <b>Universal Pigmented Plaster Primer</b>.</li> <li>• Remove all dust, foreign material, fungal and algae growth.</li> <li>• Fill and seal all visible cracks and coat with <b>Universal Pigmented Plaster Primer</b>.</li> </ul>				
<ul style="list-style-type: none"> <li>• <b>Previously Painted Surfaces</b></li> <li>• <b>Concrete</b></li> <li>• <b>Precast</b></li> <li>• <b>Plaster</b></li> </ul>	<ul style="list-style-type: none"> <li>• Remove all loose, flaking and bubbling paint.</li> <li>• Remove all dust, grease, foreign material, fungal and algae growth.</li> <li>• Allow to dry. If then powdery or friable, seal with <b>Universal Pigmented Plaster Primer</b>.</li> </ul>				

<ul style="list-style-type: none"> <li>• <b>Colour Range and Quantities</b></li> </ul>	<ul style="list-style-type: none"> <li>• Opaque Liquid</li> <li>• Available in 1ℓ, 5ℓ and 20ℓ.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Precautions</b></li> </ul>	<ul style="list-style-type: none"> <li>• This product is highly flammable and has a flashpoint of 37° Celsius.</li> </ul>
<ul style="list-style-type: none"> <li>• <b>Disclaimer</b></li> </ul>	Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.
<b>Universal Coatings (PTY) LTD</b> <b>Reg No. 1982/10922/07</b>	
<b>19 Staal Street</b> <b>Kya Sands, Randburg</b> <b>South Africa</b>	<b>Tel. +(27) 11- 462 4284</b> <b><a href="http://www.universalphaints.co.za">www.universalphaints.co.za</a></b>