Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

UNIVERSAL PINKWOOD PRIMER

PRODUCT CODE: PRIOO TECHNICAL DATA SHEET

TECHNICAL DATA SHEET November 2016.R3

•	Product Description	 An alkyd / oil based primer for interior and especially exterior wood, which has been especially formulated with oil to feed and nourish the wood so as to give the best long term performance for the total system when used to provide a very strong and stable base for over coating with a wide range of Universal decorative solvent based products. 		
•	Application Areas	• Wood		
•	Product Features	A smooth Universal Pinkwood Primer developed especially for		
		wood.		
			=	
		No mess applicat		
			can be top coated man a mac range or contental deceration	
	Due duet Dete	based products. Resin Base	Alkyd Based Resin.	
•	Product Data	Film Thickness	± 45 microns	
	Application	_	y a generous coat of Universal Pinkwood Primer to	
•	Details		the wood, which needs protecting.	
	Details		Allow to dry at least overnight before recoating (possibly longer in	
			winter, when the oil can take longer to dry).	
•	Mixing	Always stir well before use with a flat paddle.		
•	Application	The wood must be dry, seasoned, all knots and cracks to be sealed.		
	Method		·	
•	Thinning	Thinning is not recommended.		
•	Cleaning	Use Universal Mineral Turpentine.		
	General Application	Do not apply before 9:00Hr and after 16:00Hr in the winter.		
	General Application		 Do not apply to exterior if it looks like rain will occur within 4 – 6 hours 	
		of application.		
		Universal Pinkwood Primer is ready for use on un-thinned, thinning		
		with white spirits will reduce its hiding power.		
		,		
		· ·	 The spread rate will vary with porosity and type of substrate. For uncoated new work 5 -7m² / litre. 	
		 Application equipment Spirits. 	Application equipment is to be cleaned up with Universal White Spirits.	
•	Colour Range	Pink Only		
	and Quantities	• Available in 1ℓ & 5ℓ.		
•	Precautions	This product is highly flammable and has a flashpoint of 37° Celsius.		
		 This product contains no toxic substances. 		
		It should only be used in well ventilated areas, and you should not eat,		
		drink or smoke whilst using it.		
	Disalahasa	Universal Paints cannot be held liable if the product fails due to improper		
•	Disclaimer	surface preparation or application.		
	раниот ргораганон от аррноанон.			
Universal Coatings (PTY) LTD				
Reg No. 1982/10922/07				
	109 10. 1002/10022/01			
40.0(cal.0(cal.				
	19 Staal Street		Tel. +(27) 11- 462 4284	
	Kya Sands, F		www.universalpaints.co.za	
	South A	frica		

