



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

PLASTER FIX
PRODUCT CODE:PFIX00
 TECHNICAL DATA SHEET
 February 2017.1

Product Description	<ul style="list-style-type: none"> • Universal Plaster Fix is a water-based bonding aid. 	
Application Areas	<ul style="list-style-type: none"> • Plaster Fix has been designed specifically for use in the building industry to bond sand / cement plaster and gypsum plaster to smooth surfaces. 	
Product Features	<ul style="list-style-type: none"> • Improves non-structural bond of cement & gypsum plasters. • No more hacking and chipping of smooth surfaces. • Bonds to sound PVA surfaces. • Easy to use. 	
Product Data	Resin Base	Acrylic resin emulsion
	Drying Time	Touch dry +- 30 minutes Hard dry 3-4 hours
	Film Thickness	35–50 ^o microns
Application Details	<ul style="list-style-type: none"> • Apply by roller or brush - one coat only. • Allow to dry for a minimum of 3 hours before application of top coats, if air temperature drops below 10° Celsius during winter. • Allow 24 hours to dry before applying top coats. 	
Mixing	<ul style="list-style-type: none"> • Always stir well before use with a flat paddle. 	
Application Method	<ul style="list-style-type: none"> • Brush or Roller. 	
Surface Preparation	<ul style="list-style-type: none"> • Surfaces should be free of loose particles, scaling of flaking material. Wire brush & rinse the surface if necessary. 	
Application	<ul style="list-style-type: none"> • Soffits and vertical surfaces – coat the prepared surfaces with Plaster Fix after dust etc. has been removed and apply a scratch coat whilst the Plaster Fix is still wet. Allow the scratch coat to dry and then plaster in the usual manner. • Where gypsum based plaster is used, apply the Plaster Fix to the prepared surface and plaster straight onto the wet Plaster Fix finishing off in a single operation. Plaster Fix can be added to the plaster mix (10% of water content) to obtain a stronger bond. Plaster Fix can be applied by brush or roller. Coverage is ± 10 square metres per litre. 	
Disclaimer	Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.	
Universal Coatings (PTY) LTD Reg No. 1982/10922/07		
19 Staal Street Kya Sands, Randburg South Africa	Tel. +(27) 11- 462 4284 www.universalphaints.co.za	