



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

CONTRACTORS PVA WHITE

PRODUCT CODE: PVA00

TECHNICAL DATA SHEET

November 2016.R3

<ul style="list-style-type: none"> • Product Description 	<ul style="list-style-type: none"> • Universal Contractors PVA is an economical water based coating. • NB: Not for use as a base coat before application of Universal Paints Matt Acrylic top coats.
<ul style="list-style-type: none"> • Application Areas 	
<ul style="list-style-type: none"> • Product Features 	Good hiding power applied at a rate of 4 -6 m ² per litre on smooth plaster.
<ul style="list-style-type: none"> • Application Details 	<p>Uncoated concrete surfaces:-</p> <ul style="list-style-type: none"> • Remove all dust and any fungal growth. • Fill any cracks with Universal Acrylic Crack Filler. • If construction of the area to be painted is of clay stock and plaster, it is advisable to use Universal Pigmented Plaster Primer as a base coat, due to the effect of efflorescence (a leaching salt given off by the fresh clay stock brick) which cannot be contained by the use of any water based paint.
<ul style="list-style-type: none"> • Mixing 	<ul style="list-style-type: none"> • Always stir well before use with a float paddle.
<ul style="list-style-type: none"> • Application Method 	<ul style="list-style-type: none"> • Brush or roller.
<ul style="list-style-type: none"> • Thinning 	<ul style="list-style-type: none"> • Universal Contractors PVA is ready for use un-thinned; thinning with water will reduce its hiding power.
<ul style="list-style-type: none"> • Cleaning 	<ul style="list-style-type: none"> • Clean up using water.
<ul style="list-style-type: none"> • General Application 	<ul style="list-style-type: none"> • By brush or roller. • Clean up with water.
<ul style="list-style-type: none"> • Uncoated Concrete Surfaces • Raw / New Plaster • Precast 	<ul style="list-style-type: none"> • Make sure surface is dry and firm. • Remove all dust and foreign material, fungal and algae growth. • Fill and seal all cracks with Universal Acrylic Crack Filler. • Apply one coat of Universal Bonding Liquid to cover Universal Acrylic Crack Filler. • Apply two coats of Universal Contractors PVA – allowing 4 hours of drying time between coats.
<ul style="list-style-type: none"> • Colour Range and Quantities 	<ul style="list-style-type: none"> • Universal Contractors PVA is available in White only. • Available in 5ℓ & 20ℓ.
<ul style="list-style-type: none"> • Precautions 	<ul style="list-style-type: none"> • Universal Contractors PVA is non-flammable.
<ul style="list-style-type: none"> • Disclaimer 	Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.

Universal Coatings (PTY) LTD
Reg No. 1982/10922/07

19 Staal Street
Kya Sands, Randburg
South Africa

Tel. +(27) 11- 462 4284
www.universalphaints.co.za