



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

RED OXIDE Q.D.PRIMER

PRODUCT CODE: PRO00

TECHNICAL DATA SHEET

November 2016.R3

<ul style="list-style-type: none"> • Product Description 	<p>A solvent based anti-corrosive metal primer for use on degreased galvanized steel and rust free, clean dry mild steel, under a range of Universal Paints water and solvent based decorative products.</p>
<ul style="list-style-type: none"> • Application Areas 	<ul style="list-style-type: none"> • Degreased and / or weathered galvanised steel. • Rust free, clean, dry mild steel.
<ul style="list-style-type: none"> • Product Features 	<ul style="list-style-type: none"> • An anti-corrosive primer suitable for use in the harsh urban / industrial environment. • Suitable for use on degreased galvanized steel and rust free mild steel. • Excellent adhesion. • Excellent, no mess application properties. • Can be over-coated with a range of Universal Paint's decorative water and solvent based products. • Apply by brush, roller or airless spray.
<ul style="list-style-type: none"> • Application Details 	<ul style="list-style-type: none"> • Apply a generous coat of Universal Red Oxide Q.D. Primer to the area, which needs protecting. • For very severe cases e.g. in very harsh environments, 2 coats of Universal Red Oxide Q.D. Primer may be required. • Covering rate of 8 – 10m² / litre. • Allow to dry for 6 hours before recoating with Universal Paints water based products or Universal Paint's solvent based products. • Can be applied by using a brush or the spray method.
<ul style="list-style-type: none"> • Surface Preparation 	<ul style="list-style-type: none"> •
<ul style="list-style-type: none"> • Mild Steel (Renovation) 	<ul style="list-style-type: none"> • Affected areas need to be cleaned back to bright metal by hand mechanical or blast cleaning.
<ul style="list-style-type: none"> • Mild Steel (New) 	<ul style="list-style-type: none"> • Surfaces need to be abrasively degreased with Universal Zinc Cleaner to remove the manufacturer's grease protective layer. • This process is repeated until the surface is water break free. • Apply a coat of Universal Red Oxide Q.D Primer.
<ul style="list-style-type: none"> • General 	<ul style="list-style-type: none"> • Do not apply before 9:00Hr and after 16:00Hr in winter. • Do not apply to exterior if it looks like rain will occur with 4 – 6 hours of application. • Application equipment is to be cleaned with Universal Lacquer Thinners. • Universal Red Oxide Q.D. Primer should never be mixed with any other products. • Universal Red Oxide Q.D Primer can be diluted up to 10% with Universal "A" Grade Lacquer Thinners.
<ul style="list-style-type: none"> • Precautions 	<ul style="list-style-type: none"> • Product is flammable.
<ul style="list-style-type: none"> • Disclaimer 	<p>Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.</p>
<p>Universal Coatings (PTY) LTD Reg No. 1982/10922/07</p>	
<p>19 Staal Street Kya Sands, Randburg South Africa</p>	<p>Tel. +(27) 11- 462 4284 www.universalphaints.co.za</p>