



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

UNIVERSAL UNIFLOOR

PRODUCT CODE:UFL00

TECHNICAL DATA SHEET

November 2016.R3

<ul style="list-style-type: none"> • Product Description 	<p>A classical alkyd based high abrasion and alkali resistant interior matt or gloss coating for those medium traffic areas that need a highly washable and durable coating.</p>
<ul style="list-style-type: none"> • Application Areas 	<ul style="list-style-type: none"> • Concrete floors.
<ul style="list-style-type: none"> • Product Features 	<ul style="list-style-type: none"> • Highly abrasive / alkali resistant for suitably prepared concrete floors. • Highly washable, cleanable. • Excellent adhesion to all concrete substrates. • Excellent, no mess application properties, with excellent, flow and levelling. • Touch dry in less than 4 hours. • Resists mild acids and normal engine oil. • NB: This product does not resist brake fluid or hydraulic oil.
<ul style="list-style-type: none"> • Application Details 	<ul style="list-style-type: none"> • With a brush or mohair roller, apply a generous coat of Universal Unifloor to the area which needs protecting. • Allow to dry 18 – 24 hours before recoating. • Apply a second generous coat. • Clean-up application equipment with Universal Mineral Turpentine or brush cleaner. • Only apply in ventilated areas, keep away from all ignition sources, flames and sparks. • Do not eat, drink or smoke while applying.
<ul style="list-style-type: none"> • General Application 	<ul style="list-style-type: none"> • Do not apply before 9:00Hr and after 16:00Hr in winter. • Universal Unifloor is ready for use un-thinned. • 2 coats of Universal Unifloor are used for best results. • Although the spreading rate will vary with porosity and type of substrate, for uncoated new, work on 6 -8m² / litre for subsequent coats. • Application clean-up is with Universal Mineral Turpentine.
<ul style="list-style-type: none"> • Uncoated Concrete Surfaces 	<ul style="list-style-type: none"> • Remove all dust, foreign material and traces of oil. • If floor is very smooth, acid wash with a 30% solution of hydrochloric acid. • Wash off all traces of acid wash and allow to dry for at least 3 days.
<ul style="list-style-type: none"> • Colour Range and Quantities 	<ul style="list-style-type: none"> • Universal Unifloor is available in matt or gloss. • Available in 1ℓ & 5ℓ.
<ul style="list-style-type: none"> • Precautions 	<ul style="list-style-type: none"> • This product is highly flammable and has a flashpoint of 37^o Celsius.
<ul style="list-style-type: none"> • Disclaimer 	<p>Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.</p>

Universal Coatings (PTY) LTD
Reg No. 1982/10922/07

19 Staal Street
Kya Sands, Randburg
South Africa

Tel. +(27) 11- 462 4284
www.universalphaints.co.za