



Universal Coatings (Pty) Ltd | Reg No: 1982/10922/07

UNIVERSAL WATER BASED PIGMENTED PLASTER PRIMER

PRODUCT CODE: PRI01

TECHNICAL DATA SHEET

July 2018.R1

<ul style="list-style-type: none"> • Product Description 	<ul style="list-style-type: none"> • A water based interior, exterior plaster primer for masonry, cement, and plaster substrates suitable for Rhinolite Gypsum Plaster. • For use under a range of Universal Paints topcoats. 				
<ul style="list-style-type: none"> • Application Areas 	<ul style="list-style-type: none"> • New and weathered plaster, hardboard and fibre cement walls. 				
<ul style="list-style-type: none"> • Product Features 	<ul style="list-style-type: none"> • Serves as both a sealer and a primer. • Excellent adhesion to a range of substrates. • Excellent, no mess application properties. • High Alkali resistant. • A one coat application. • Not suitable for ferrous metal, non-ferrous metal or plastic and laminated or ceramic substrate applications. 				
<ul style="list-style-type: none"> • Product Data 	<table border="1"> <tr> <td>Resin Base</td> <td>Acrylic Resin</td> </tr> <tr> <td>Drying Time</td> <td>Indoors – 2 Hours Outdoors 1 hour</td> </tr> </table>	Resin Base	Acrylic Resin	Drying Time	Indoors – 2 Hours Outdoors 1 hour
Resin Base	Acrylic Resin				
Drying Time	Indoors – 2 Hours Outdoors 1 hour				
<ul style="list-style-type: none"> • Application Details 	<ul style="list-style-type: none"> • With a brush, mohair roller or airless spray. • Apply a generous coat of Universal Water Based Pigmented Plaster Primer to the area which needs protecting. • Allow to dry 4 hours before recoating. • Clean up application equipment with water. • Only apply in ventilated areas. • Do not eat, drink or smoke while applying. 				
<ul style="list-style-type: none"> • Mixing 	<ul style="list-style-type: none"> • Always stir well using a flat paddle. 				
<ul style="list-style-type: none"> • Application Method 	<ul style="list-style-type: none"> • Brush or roller. 				
<ul style="list-style-type: none"> • Thinning 	<ul style="list-style-type: none"> • Thinning is not recommended. 				
<ul style="list-style-type: none"> • Cleaning 	<ul style="list-style-type: none"> • Clean with water. 				
<ul style="list-style-type: none"> • General Application 	<ul style="list-style-type: none"> • Do not apply outdoors before 9:00Hr and after 16:00Hr in winter. • Do not apply to exterior if it looks like rain will occur with 4 – 6 hours of application. • Universal Water Based Pigmented Plaster Primer Is ready for use un-thinned; thinning will reduce its hiding and adhesion abilities. • Although the spreading rate will vary with porosity and type of substrate. For uncoated new work the spread rate for Universal Water Based Pigmented Plaster Primer is 4 – 6m² /litre. • Clean up application equipment with clean water. 				
<ul style="list-style-type: none"> • Uncoated Concrete Surfaces • Raw / New Plaster • Precast 	<ul style="list-style-type: none"> • Remove all dust, foreign material, fungal, algae growth. • Fill and seal all visible cracks and coat with Universal Water Based Pigmented Plaster Primer. • Remove all dust, foreign material, fungal and algae growth. • Fill and seal all visible cracks and coat with Universal Water Based Pigmented Plaster Primer. 				
<ul style="list-style-type: none"> • Previously Painted Surfaces • Concrete • Precast • Plaster 	<ul style="list-style-type: none"> • Remove all loose, flaking and bubbling paint. • Remove all dust, grease, foreign material, fungal and algae growth. • Allow to dry. If then powdery or friable, seal with Universal Water Based Pigmented Plaster Primer. 				

Water Based Pigmented Plaster Primer

Page 1 of 2

The **COLOUR** *of Quality.*

<ul style="list-style-type: none"> • Colour Range and Quantities 	<ul style="list-style-type: none"> • Opaque Liquid • Available in 1ℓ, 5ℓ and 20ℓ.
<ul style="list-style-type: none"> • Precautions 	<ul style="list-style-type: none"> • Universal Water Based Pigmented Plaster Primer is non-flammable.
<ul style="list-style-type: none"> • Disclaimer 	<p>Universal Paints cannot be held liable if the product fails due to improper surface preparation or application.</p>
<p>Universal Coatings (PTY) LTD Reg No. 1982/10922/07</p>	
<p>19 Staal Street Kya Sands, Randburg South Africa</p>	<p>Tel. +(27) 11- 462 4284 www.universalphaints.co.za</p>